

GRABBER GT PLUS

ANYWHERE
IS **POSSIBLE**

**FEEL CONFIDENT
ON ANY TERRAIN!**

Equipped with exceptional robustness and enhanced durability, the new **GRABBER GT PLUS** is your perfect partner for making every ride an enjoyable experience!

SINCE 1915.
GENERAL TIRE. A BRAND OF CONTINENTAL.



GENERAL TIRE

WWW.GENERALTIRE.EU

THE NEW GRABBER GT PLUS.

ENJOY INCREDIBLE STABILITY WITH OUR NEW SUV TYRE FOR KEEPING CONTROL ON ANY RIDE!

SUV-DEDICATED ROBUSTNESS

Stay relaxed on every journey.

No more challenging road conditions! Benefit from an incredibly sturdy design that provides greater stability than a conventional on-road tyre of the same size. Just settle in at the wheel and forget about kerb damage or rough terrain. With its exceptional robustness, your tyre is sure to deliver a worry-free ride.



OUTSTANDING WET GRIP

Stay on the safe side whatever the weather.

With the GRABBER GT PLUS, there is no such thing as so-called "bad weather." Thanks to its excellent traction, your tyre will keep you feeling safe even in heavy rain. The GRABBER GT PLUS couldn't care less what the weather forecast says; it simply serves up a whole new level of reliability.



HIGH MILEAGE

Your companion for countless miles.

Unreachable distances don't exist. The GRABBER GT PLUS will accompany you on any trip you care to take. With its matchless durability, this tyre will carry you wherever you want to go, no matter how far away it may be.



GENERAL TIRE'S TECHNOLOGIES



No need to worry about tyre damage. The steel belts of this tyre provide added stability and protect it, especially from kerb damage.







Always know when to replace your tyre. The RTM (Replacement Tyre Monitor) provides you with added safety: Before the minimum tread depth is reached, the inscription will change to REPLACE TYRE.



Keep your tyres intact. The VAI (Visual Alignment Indicator) helps you avoid uneven tyre wear. If the sipes of the VAI show uneven wear, your wheel alignment needs checking.

GRABBER GT PLUS THE FULL RANGE

Rim diameter	Size ¹⁾	Permitted rim widths (in inch)	Tyre dimensions Max. standard value in operation		Rolling circumference + 1.5% - 2.5% (mm)					
			width (mm)	outer diameter (mm)						
15"	195/80 R 15 96H	5.0 – 6.5	204	705	2114	D	A	71/B	-	
	205/70 R 15 96H	5.0 – 7.0	217	681	2040	tbd ²⁾	tbd ²⁾	tbd ²⁾	-	
16"	205/80 R 16 104T XL	5.0 – 7.0	211	748	2239	E	C	72/B	-	
	215/70 R 16 100H	5.5 – 7.0	230	720	2159	C	A	71/B	-	
	225/70 R 16 103H	6.0 – 7.5	237	734	2202	C	A	71/B	-	
	235/70 R 16 106H	6.0 – 8.0	250	750	2245	C	A	71/B	-	
	245/70 R 16 111H XL	6.5 – 8.0	258	764	2288	C	A	72/B	-	
	255/70 R 16 111H	6.5 – 8.5	270	778	2330	C	A	72/B	-	
	265/70 R 16 112H	7.0 – 9.0	283	792	2373	C	A	72/B	-	
	215/65 R 16 98H	6.0 – 7.5	230	698	2092	C	A	71/B	-	
	215/65 R 16 102V XL	6.0 – 7.5	230	698	2092	C	A	72/B	-	
	255/65 R 16 109H	7.0 – 9.0	270	752	2251	C	A	72/B	-	
235/60 R 16 100H	6.5 – 8.5	250	700	2098	C	A	71/B	-		
17"	225/65 R 17 102H	6.0 – 8.0	237	736	2208	C	A	71/B	-	
	225/65 R 17 106V XL	6.0 – 8.0	237	736	2208	C	A	72/B	-	
	235/65 R 17 108V XL	6.5 – 8.5	250	750	2251	C	A	72/B	-	
	245/65 R 17 111V XL	7.0 – 8.5	258	762	2288	C	A	72/B	-	
	255/65 R 17 110H	7.0 – 9.0	270	778	2330	C	A	72/B	-	
	265/65 R 17 112H	7.5 – 9.5	283	790	2367	C	A	72/B	-	
	215/60 R 17 96H	6.0 – 7.5	230	700	2105	C	A	71/B	-	
	215/60 R 17 96V	6.0 – 7.5	230	700	2105	C	A	71/B	-	
	215/65 R 17 99V	6.0 – 7.5	230	724	2172	C	A	71/B	-	
	225/60 R 17 99V	6.0 – 8.0	237	712	2141	C	A	71/B	-	
	235/60 R 17 102V	6.5 – 8.5	250	726	2178	C	A	71/B	-	
	235/55 R 17 99H	6.5 – 8.5	255	700	2105	C	A	71/B	-	
	235/55 R 17 99V	6.5 – 8.5	255	700	2105	C	A	71/B	-	
	275/55 R 17 109V	7.5 – 9.5	295	746	2239	C	A	72/B	-	
18"	225/60 R 18 100H	6.0 – 8.0	237	737	2217	C	A	71/B	-	
	235/60 R 18 103V	6.5 – 8.5	250	751	2254	C	A	71/B	-	
	235/60 R 18 107W XL	6.5 – 8.5	250	751	2254	C	A	72/B	-	
	255/60 R 18 112V XL	7.0 – 9.0	270	775	2327	C	A	73/B	-	
	215/55 R 18 99V XL	6.0 – 7.5	235	703	2114	C	A	72/B	-	
	225/55 R 18 98V	6.0 – 8.0	242	715	2150	C	A	71/B	-	
	235/55 R 18 100H	6.5 – 8.5	255	725	2181	C	A	71/B	-	
	235/55 R 18 100V	6.5 – 8.5	255	725	2181	C	A	71/B	-	
	255/55 R 18 109Y XL	7.0 – 9.0	276	749	2248	C	A	73/B	-	
	235/50 R 18 97V	6.5 – 8.5	255	703	2114	C	A	71/B	-	
	235/50 R 18 101Y XL	7.0 – 8.5	255	703	2114	C	A	72/B	-	
	19"	225/55 R 19 99V	6.0 – 8.0	242	741	2230	C	A	71/B	-
		235/45 R 19 99W XL	8.0 – 9.0	245	703	2120	C	A	72/B	-
235/55 R 19 105V XL		6.5 – 8.5	255	751	2260	C	A	72/B	-	
235/55 R 19 105Y XL		6.5 – 8.5	255	751	2260	C	A	72/B	-	
255/55 R 19 111V XL		7.0 – 9.0	276	775	2327	C	A	73/B	-	
255/55 R 19 111Y XL		7.0 – 9.0	276	775	2327	C	A	73/B	-	
235/50 R 19 99V		6.5 – 8.5	255	729	2193	C	A	71/B	-	
255/50 R 19 107Y XL		7.0 – 9.0	276	749	2254	C	A	73/B	-	
265/50 R 19 110Y XL		7.5 – 9.5	288	759	2284	C	A	73/B	-	
275/45 R 19 108Y XL		8.5 – 10.5	284	741	2230	C	A	73/B	-	
285/45 R 19 111W XL		9.0 – 10.5	296	749	2254	C	A	75/B	-	
20"	245/45 R 20 103Y XL	8.0 – 9.0	253	736	2220	C	A	72/B	-	
	255/45 R 20 105Y XL	8.0 – 9.5	265	748	2251	C	A	73/B	-	
	265/45 R 20 108Y XL	8.5 – 10.0	277	756	2275	C	A	73/B	-	
	275/45 R 20 110Y XL	8.5 – 10.5	284	766	2306	C	A	73/B	-	
	255/50 R 20 109Y XL	7.0 – 9.0	276	774	2330	C	A	73/B	-	
	255/55 R 20 110Y XL	7.0 – 9.0	276	800	2403	C	A	73/B	-	
	275/40 R 20 106Y XL	9.0 – 11.0	289	736	2220	C	A	73/B	-	
	315/35 R 20 110Y XL	10.5 – 12.5	333	736	2220	C	A	75/B	-	
21"	295/35 R 21 107Y XL	10.0 – 11.5	313	747	2254	C	A	75/B	-	
	255/40 R 21 102Y XL	8.5 – 10.0	270	745	2248	C	A	73/B	-	
	265/40 R 21 105Y XL	9.5 – 10.5	282	753	2272	C	A	73/B	-	
	275/45 R 21 110Y XL	9.0 – 10.5	284	791	2382	C	A	73/B	-	
22"	275/40 R 22 108Y XL	9.0 – 11.0	289	787	2376	C	A	73/B	-	
	23"	285/35 R 23 107Y XL	9.5 – 11.0	302	792	2391	C	A	75/B	-
		305/30 R23 105W XL	10.5 – 11.5	326	725	2187	C	A	75/B	-

¹⁾ All sizes with rim protection (FR)

²⁾ to be decided

